

ROCK 210

TEMPORARY FLOOR PROTECTION FOR CONSTRUCTION SITES STANDARDIZED - WITH FIRE CERTIFICATION

- IDEAL for establishments open to public and STORES
- STANDARD COLORS and ROLLS
- FLOORS PROTECTION by cushioning the impact caused by falling objects
- FIRE RESISTANCE
- ABSORPTION of SURROUNDING DUST











BREATHABLE LI MATERIAL



LIQUIDS PARTIAL ABSORPTION



EASY TO CUT



ECO-DESIGN: MANUFACTURED WITH 100% RECYCLED FIBRES



LOW COST







TECHNICAL DATA

Surface: flat needlepunch protective textile

Fibres: 100% recycled polyester

Backing: impregnated

Total weight: $210 \text{ g/m}^2 \pm 10\%$ Dimensions: $2 \times 50 \text{ m} / 4 \times 50 \text{ m}$

Installation: loose laid

REFERENCES

Dimensions	Sommer codes	EAN codes
2 x 50 m	ROCKC2	370037 9022661

Available in 4 x 50 m (minimum order 1000 m²).

Please contact us.





* Information on emission of volatile substances in an interior, which represent a risk of inhalation on a scale starting from A+ (almost no emission) to C (high emission)

Loose laid on any A2fl or A1fl class substrate







SOMMER NEEDLEPUNCH

341, rue de la Mairie 59780 BAISIEUX - France